

Qty. Description

1 UP 20-07 N 150



Note! Product picture may differ from actual product

Product No.: [59640506](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid.

The pump is characterized by:

- * Ceramic shaft and radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can and bearing plate.

Impeller: * Corrosion-resistant impeller, Composite, PES/PP.

Pump housing: * Stainless steel pump housing.

Phase: The motor is a 1-phase motor.

No additional motor protection is required.

Liquid:

Pumped liquid: Water

Liquid temperature range: 2 .. 110 °C

Selected liquid temperature: 60 °C

Density: 983.2 kg/m³

Technical:

TF class: 95

Approvals on nameplate: CE, VDE, EAC, WEEE

Materials:

Pump housing: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Impeller: Composite, PES/PP

Installation:

Amb. max at 80 dgr C liquid: 80 °C

Maximum operating pressure: 10 bar

Pipe connection: G 1 1/4

Pressure rating: PN 10

Port-to-port length: 150 mm

Electrical data:

Max. power input: 50 W

Mains frequency: 50 Hz

Rated voltage: 1 x 230 V

Current in speed 3: 0.24 A

Capacitor size - run: 4 µF



Company name:

Created by:

Phone:

Date:

01/10/2020

Qty.	Description
	<p>Enclosure class (IEC 34-5): IP44 Insulation class (IEC 85): F</p> <p>Others:</p> <p>Net weight: 2.1 kg Gross weight: 2.3 kg Shipping volume: 0.004 m³ Danish VVS No.: 380611000 Finnish LVI No.: 4615602 Norwegian NRF no.: 9042207</p>