Since 1892 Bofill

Ø80>300

Simple Pared Serie 200
200 Series Single Wall

Serie 200 / *200 series*

ASD

Adaptador
Adapter

Ø	A	B	
80	79	82	
125	124	127	
150	149	152	
175	174	177	
200	199	202	
250	249	252	
300	299	302	

Unidades expresadas en mm
Units are in mm



Aplicaciones-Applications

Elemento adaptador para conectar en sentido de los humos de la serie 200 a la serie doble pared. Esta pieza tiene que ir acompañada con un EDP (no incluido) para tapar la lana. Posibilidad de ampliar el diámetro y al mismo tiempo pasar de simple pared serie 200 a doble pared.

Adapter element to connect in the direction of the fumes of the 200 series to the double wall series. This piece has to be accompanied with an EDP (not included) to cover the wool. Possibility of extending the diameter and at the same time going from simple wall series 200 to double wall.

TDCI

Adaptador doble cono
Double cone adapter

Ø	A	B	C
80			
100			
125			
150			
175			
200			
250			
300			

Unidades expresadas en mm
Units are in mm



Aplicaciones-Applications

Elemento tubo con doble cono para el desvío de condensados hacia dentro de la caldera o estufa y evitar que salgan al exterior. Ambos lados son hembra.

Element tube with double cone for the deviation of condensates into the boiler or stove and prevent them from going outside. Both sides are female.

AI

Brida
Clamp

Ø	B		
80	80		
100	100		
110	110		
120	120		
125	125		
130	130		
150	150		
175	175		
180	180		
200	200		
250	250		
300	300		

Unidades expresadas en mm
Units are in mm



Aplicaciones-Applications

Elemento de fijación de la chimenea en la pared interior del edificio.

Fixing element of the chimney on the interior wall of the building.