

SERIE PRESSCONTROL

Modelo Model Modèle	Cod.	Tensión Voltage (V)	I max. (A)	CV _{MAX}	Q _{MAX} (l/h)	Q _{MIN} (l/h)	P _{ARRANQUE} P _{START} P _{DÉMARRAGE} (bar)	P _{PARO} P _{STOP} P _{ARRÊT} (bar)	P _{MAX} (bar)	Conexiones Connections Connexions	Homologación Agreement Homologation
PRESSCONTROL mini (ECOPRESS)	2212	1~230Vac	6	1 CV	7000	60	0,8	Máxima de la bomba <i>Maximum of pump</i> <i>Maximale de la pompe</i>	10	1" M	CE
PRESSCONTROL	2213	1~230Vac	8	1,5 CV	7000	60	1,5		10	1" M	CE - VDE
MASCONTROL	2216	1~230Vac	16	3 CV	10000	60	1,5		10	1¼" M	CE - VDE
MASCONTROL-UP	2220	3~400Vac 3~230Vac	6	3 CV	10000	60	1,5		12	1¼" M	CE - VDE
MASCONTROL 24 V.	2296	24 Vcc	20	1 CV	7000	60	1,5		10	1¼" M	CE - VDE
RP-90	2210	1~230Vac	10	1 CV	7000	60	1,5		6	1" M	-
CONTROLPRES REGULABLE	2235	1~230Vac	16	3 CV	10000	60	1,5	Regulable de 3 - 6,5 BAR	10	1¼" M	CE - VDE

Bajo demanda se puede modificar la presión de arranque, la tensión de alimentación (12-24-230 V.) y la membrana para utilizar el regulador en trasvases de gas-oil.